

FPF-ACCFG-5

FOOD GRADE AIR COMPRESSOR CLEANER AND LUBRICANT

FPF-ACCFG-5 functions as both a fully formulated food-grade compressor lubricant and a cleaner, providing excellent cleaning properties and outstanding protection. Intended for use in varnished and carboned screw compressors, FPF-ACCFG-5 will typically clean a compressor in approximately 2,000 hours. It is designed to not disrupt normal operations and to minimize filter and separator blockage. FPF-ACCFG-5 meets H1 requirements for lubricants with incidental food contact (FDA 21 CFR 178.3570).

ATTRIBUTES

- Food-grade formulation
- Fully formulated cleaner and lubricant
- Protects against wear
- Oxidatively stable
- High flash point
- Low volatility
- Excellent film strength
- Controls carbon and varnish formation
- Non-toxic/non-hazardous

TYPICAL LUBRICANT PROPERTIES

| Lubrication Properties | FPF-ACCFG-5-46 | FPF-ACCFG-5-68 | FPF-ACCFG-5-100 |
|-------------------------|----------------|----------------|-----------------|
| Viscosity cSt @ 0°C | 599 | 982 | 1735 |
| Viscosity cSt @ 40°C | 46 | 68 | 103 |
| Viscosity cSt @ 60°C | 20.7 | 29 | 41.6 |
| Viscosity cSt @ 80°C | 11.2 | 15 | 20 |
| Viscosity cSt @ 100°C | 6.9 | 8.9 | 11.8 |
| Flash Point °F (°C) | 440 (226) | 455 (235) | 495 (257) |
| Copper Corrosion, 24 Hr | 1a | 1a | 1a |

Pro Fluid lubricants do not validate warranty coverage for FS-Curtis products

FS-CURTIS | 1905 Kienlen Avenue | St. Louis, MO 63133
314-383-1300 | www.fscurtis.com