

PRO FLUID



FSC-SFFG-5

FOOD-GRADE FLUSHING FLUID

FSC-SFFG-5 food-grade flushing fluid is designed to flush old food-grade oil from a compressor system. It is highly recommended for use when changing from a non food-grade compressor fluid to an Isel food-grade compressor fluid.

FSC-SFFG-5 is not suitable for flushing polyalkylene glycol (PAG) compressor lubricants.

ATTRIBUTES

- High flash point
- High viscosity index
- Good film strength
- Excellent rust control
- Non-toxic/non-hazardous
- Food-grade Formulation

TYPICAL LUBRICANT PROPERTIES

Lubrication Properties	FSC-SFFG-5
Viscosity cSt @ 0°C	336
Viscosity cSt @ 40°C	32
Viscosity cSt @ 60°C	15.2
Viscosity cSt @ 80°C	8.5
Viscosity cSt @ 100°C	5.4
Flash Point °F (°C)	430 (221)
Demulsibility, 54.4°C, 30 Min	40/40/0
Copper Corrosion,	1a

Pro Fluid lubricants do not validate warranty coverage for FS-Curtis products

FS-CURTIS | 1905 Kienlen Avenue | St. Louis, MO 63133
314-383-1300 | www.fscurtis.com

The information on FS-Curtis and competitive products provided should only be used as a general guide. Lubricant properties are typical results and should not serve as a sole resource for determining the correct lubricant for a particular application. Please consult a FS-Curtis representative to ensure that the product is the correct choice for the application. Revised 03/2016